

Model	Bending Force	Bending Length	Distance Between Columns	Throat Depth	Slide Stroke	Open Height
	KN	mm	mm	mm	mm	mm
2-400-4000	4000	5000	3100	500	300	610
2-400-5000		6000	3800	500	300	610
2-400-6000		4000	4800	500	300	610
2-500-4000	5000	5000	3100	500	300	610
2-500-5000		6000	3800	500	300	610
2-500-6000		4000	4800	500	300	610
2-600-4000	6000	5000	3100	600	320	650
2-600-5000		6000	3800	600	320	650
2-600-6000		6000	4800	600	320	650
2-800-6000	8000	8000	4800	600	320	800
2-800-8000			6600	600	320	800

Main Motor	Tank Volume	Approaching Speed	Progress Rate	Return Speed	Machine Length	Machine Width
KW	L	mm/s	mm/s	mm/s	mm	mm
30	700	65	8	80	4300	2700
30	700	65	8	80	5300	2700
30	700	65	8	80	6300	2700
37	800	100	8	80	4300	2700
37	800	100	8	80	5300	2700
37	800	100	8	80	6300	2700
45	1000	90	8	90	4300	3300
45	1000	90	8	90	5300	3300
45	1000	90	8	90	6300	3300
60	1800	90	8	90	6300	3500
60	1800	90	8	90	8300	3600

Machine Height mm
3500
3700
3900
3500
3700
4000
3900
4200
4500
4000
4500